

Audits

The audits API URL is designed to return a list of all audits with the following fields:

```
audits/
    <str>                'name',
    <int>                'id',
    <str>                'status',
    <str>                'additional_signature_print',
    <str>                'additional_signature_position',
    <str - URL>          'signature',
    <int>                'asset_id',
    <str>                'asset_name',
    <str - Date>         'updated_at',
    <bool>               'close_audit_enabled',
    <str>                'latitude',
    <str>                'signature_position',
    <str - URL>          'report',
    <str - Date>         'closed_at',
    <str>                'closed_notes',
    <str - URL>          'closed_by_signature',
    <str>                'status_color',
    <str - Date>         'completed_at',
    <int>                'closed_by_id',
    <str - Date>         'created_at',
    <str>                'state',
    <str>                'longitude',
    <str>                'signature_print',
    <bool>               'additional_signature',
    <bool>               'compliant',
    <bool>               'status_changed_on_close',
    <str>                'device',
    <str - Date>         'published',
    <int>                'auditor_id',
```

```
<str> 'notes',
<Observation Array> 'observations',
<str> 'audit_result'
```

Observation:

```
<int> 'question_id',
<str> 'question_text',
<str> 'requirement_identifier',
<NonConformance Array> 'nonconformances',
<CustomResponse Array> 'custom_responses',
<str> 'observation',
<str> 'recommendation',
<str - Array> 'responses',
<str - Date> 'observation_start_time',
<str - Date> 'observation_end_time',
<str> 'custom_dropdown'
```

CustomResponse:

```
<int> 'custom_option_id',
<str> 'field_label',
<str> 'field_value'
```

NonConformance:

```
<int> 'nonconformance_id',
<str> 'status',
<bool> 'overdue',
<str> 'non_conformance',
<str - Date> 'complete_by',
<str - Date> 'approved_date',
<str - Date> 'created_at',
<int> 'assigned_to',
<int> 'assigned_by',
<int> 'approved_by'
```

This endpoint can be accessed via the <https://api.auditcomply.com/audits/> endpoint URL. An explanation of the fields can be found below:

- name – The name of the audit.
- id
- status – If the Audit has passed or failed based on grading used.
- additional_signature_print – Printed name of the second signatory. (if available)
- additional_signature_position – Additional signature user 'title'. (if available)
- signature – URL link to first signature.
- asset_id – ID of the asset the audit is on.
- asset_name – Name of the asset the audit is on.
- updated_at – When the audit was last updated.
- close_audit_enabled
- latitude – The latitude of where the audit was conducted. (if available)
- signature_position – Signature user 'title'.
- report – URL link to the generated PDF report of the audit.
- closed_at – When the audit was closed.
- closed_notes – Comment made on closing of the audit.
- closed_by_signature – URL link to audit closer signature.
- status_color – The color used by the audit's status
- completed_at – When the audit's requirements were all answered.
- closed_by_id – ID of the user who closed the audit.
- created_at – When the audit was created.
- state – The state in which the audit is currently in (closed, in review, ready to close etc)
- longitude – The longitude of where the audit was conducted. (if available)
- signature_print – Printed name of the first signatory.
- additional_signature – URL link to second signature. (if available)
- compliant – If the audit is compliant based on the grading used.
- status_changed_on_close
- device – Device type which the audit was submitted from. (IOS, Android, Desktop)
- published – When the audit was submitted.
- auditor_id – ID of the auditor user.
- notes – Submission Comments.
- observations – List of answered questions.
- audit_result – The score of the audit.

Observation:

- question_id – ID of the question.
- question_text
- requirement_identifier – The decimal representation of the question. (eg. 1.1 for section 1 question 1)
- nonconformances – A list of NonConformances attached to this answers.
- custom_responses – A list of answers to custom response fields.
- observation – The text of the answer.
- recommendation – The recommendation text.
- responses – The response labels for the question. (eg. yes/no/compliant)
- observation_start_time – When the answering of the question was started.
- observation_end_time – When the answering of the question was finished.
- custom_dropdown – The value of the custom dropdown for the answer. (if available)

CustomResponse:

- custom_option_id – The ID of the custom response item.
- field_label – The name of the custom response item.
- field_value – The value of the custom response.

NonConformance:

- nonconformance_id – The ID of the NonConformance.
- status
- overdue – If the NonConformance's due date has elapsed.
- non_conformance – The text of the NonConformance.
- complete_by – When the NonConformance is due.
- approved_date – When the NonConformance was approved.
- created_at – When the NonConformance was created.
- assigned_to – Who the NonConformance is assigned to.
- assigned_by – Who the NonConformance was assigned by.
- approved_by – Who the NonConformance was approved by.